

Quadralite Navigator X2 C

Navigator X2 C trigger is the ultimate controller for all Quadralite X wireless system devices. Thanks to its large backlit dot matrix LCD screen the User can control up to 5 flash groups simultaneously including its zoom function, flash exposure compensation and modeling light status. Device is equipped with set of five direct action buttons to make work with multiple light set-up easy, fast and comfortable. Ergonomically located control dial ensures precise control over flash power output and other major functions. Built in AF assist light* supports camera's auto-focus adjustment that can be compromised in poor lighting conditions.

Navigator X2 C is fully compatible with Canon automatic TTL flash light metering system** and can be used with all Quadralite TTL-capable flashes. Furthermore it can control lights in manual mode (M) and Multi (stroboscopic) modes as well. User can set flash exposure compensation or adjust flash energy output manually. High-Speed Sync and Second Curtain Sync is also supported***.

Device is equipped with USB Type-C port for firmware updates and run on two AA batteries for convenience.

Navigator X2 C features:

- Compatible with Canon automatic TTL flash light metering system**
- Ultimate radio controller for all Quadralite X wireless system devices
- 2.4 GHz wireless transmission ensures stable work on longer distances both in studio and on location (up to 100m)
- 32 communication channels and 16 groups for fast configuration and control over many lights
- TCM function ensure fast conversion of TTL settings to Manual values for exposure accuracy
- AF assist helps to adjust focus distance in poor light conditions*
- Large backlit LCD screen can display 5 groups settings simultaneously
- HSS (High Speed Sync) up to 1/8000*
- Firmware update is possible through built-in USB-C Type port

Specification

Model	Quadralite Navigator X2 C
Product type	TTL&HSS-capable radio trigger
Compatible with	Canon EOS
Flash Modes	TTL/M/Multi/OFF**
High Speed Sync	up to 1/8000 s**
Range	100 m
Frequency	2.4 GHz
Mode	Master
Channels	32
Groups	16
Power source	2 x AA
Sync socket	2.5mm Jack
Firmware upgrade	Yes (via USB-C Port)
Ready indicator	Visual
Display	Dot-matrix hi-contrast LCD
Operating temperature range	+10°C to +0°C
Length x Height x Width	90 x 58 x 50 mm
Weight	80 g (battery not included)

* This function is available only for Canon, Nikon and Sony SLT cameras

** Transmitter variant must be properly matched with specific camera brand for full compatibility. Canon transmitter will not work with Nikon camera and vice-versa.

*** TTL and HSS functions will work only when Navigator X2 is connected with TTL and HSS-capable flash such as: Atlas 600, Reporter 360 TTL or Stroboss 60evo.



Warranty: 2 years

Kit includes:

- Navigator X2 C transmitter
- Instruction manual