

Quadralite Stroboss 60 II Kit

The legendary Quadralite Stroboss 60evo model has lived to see a worthy successor! Modern and versatile reporter lamp **Quadralite Stroboss 60 II** was designed with the most demanding users in mind. The photographer's work becomes more pleasant and faster, thanks to a well-thought-out design and an even better interface.

Product Key features:

- Compatible with Canon/Nikon/Sony/Fujifilm/MFT cameras (flash exposure correction, HSS short shutter speed sync, flash bracketing, flash exposure lock, first or second curtain shutter sync),
- compatible with TTL automatic flash light metering
- compatible with E-TTL Wireless Flash remote triggering and control system (MASTER, SLAVE),
- built-in transmitter and receiver of Quadralite Navigator X remote control and triggering system (MASTER or SLAVE operation possible),
- possibility of triggering with photocells or via 2.5mm jack connector,
- high flash power (GN 60) and stable color temperature (5600K $\pm$ 200K),
- flash power adjustment in manual mode 1/1-1/128 in 1/3 EV increments),
- movable torch head (0° to 330° horizontally, -7° to 120° vertically),
- 20-200 mm zoom and built-in diffuser panel up to 14 mm,
- powered by 4xAA battery - up to 330 flashes with full flash power,
- short charging time (<2.6s),
- possibility to update firmware via USB Type-C connection.

Kit includes:

- Quadralite Stroboss 60 II lamp
- Cover
- Stand
- Original packaging



Product card



Quadralite Stroboss 60 II Kit

Description

The modern and versatile Quadralite Stroboss 60 II speedlite reporter flash, with a guide number of 60m, is designed for the most demanding users. The photographer's work becomes more enjoyable and faster, thanks to a well-thought-out design and an even better interface. Modern solutions support the creative process. With the Quadralite Stroboss 60 II flash you will save valuable time and change the way you work with flash lighting. The C version of the model is compatible with the E-TTL / E-TTL II system.

With 10-stage flash power control, the second generation of the flash provides easier adjustment to any lighting conditions. Controlling flash power from 1/1 to 1/128 gives you incredible flexibility to work in any lighting conditions.

The TCM (TTL Converted to Manual) function, which allows instant conversion from TTL mode to manual mode. This function helps lock in the correct exposure value and is useful for quickly determining a good starting point in manual flash setup.

On the 60 II you'll find the highly regarded interface known from the Quadralite V1. The clear LCD screen, thanks to the backlighting function, remains readable even in the dark. The buttons have received a more intuitive layout, making it even easier to use the flash even with gloves on. After just one use of the Quadralite 60 II, you won't want to go back to another model.

Trigger work has never been so simple and efficient. Work with one or multiple flashes simultaneously. With the Quadralite Navigator X 2.4 Ghz radio system, you'll trigger flashes up to 100m away, with support for 32 channels and up to five groups. The new 60evo II can operate as both a MASTER and SLAVE flash. Stroboss 60 II is an addition to the Quadralite ecosystem (full cooperation with reporter and studio lights).



Product card



Quadralite Stroboss 60 II Kit

Specification:

	Quadralite Stroboss 60 II Kit
Compatible systems	Canon/Nikon/Sony/Fujifilm/MFT
Guide number (ISO100, 200mm)	60
Zoom	20-200 mm, 14 mm with extended diffuser panel (for 35 mm format)
Flash head til/swing	Horizontal: from 0° to 330°, vertical: from -7° to 120°
Flash modes	E-TTL II/M/Multi/S1/S2/Master/Slave
Groups/Channels	5/32
Control range of flash energy in M	7 f-stops, 1/1 – 1/128 in 1/3 EV intervals
Recycle time	<2,6 s
Color Temperature	5600 K ± 200 K
Flash Duration t0.1	Od 1/300 (1/1) ~ 1/20000 s (1/128)
Max sync speed	High Speed Shutter Synchronization (HSS) up to 1/8000 s
Triggering Method	Optical (Master flash control)
	Wireless (with Navigator X receiver)
Display	LCD
Power supply	4xAA (R-6) not included
Battery Efficiency	Approx. ~330 flashes at full power
Dimensions	195x75x59 mm
Weight (incl. Battery)	530g



Product card

Quadralite Stroboss 60 II Kit



Compatible systems with Quadralite Stroboss 60 II Kit:

For system	Kit Name	EAN CODE
Canon	Quadralite Stroboss 60 II Canon	5901698720391
Nikon	Quadralite Stroboss 60 II Nikon	5901698720407
Sony	Quadralite Stroboss 60 II Sony	5901698720414
Fujifilm	Quadralite Stroboss 60 II Fuji	5901698720438
MFT	Quadralite Stroboss 60 II MFT	5901698720421



