

Quadralite Stroboss 60 S

Stroboss 60 S is a classic, compact reporter speedlite with the guide number of 60m and an integrated Navigator X radio control system. The flash may work with Sony ADI automatic flash metering systems. As a result, it can be easily used in automatic and semi-automatic shooting modes. Moreover, it allows for fully manual control over the flash output and zoom. Stroboss 60 S stands out with an integrated transmitter/receiver of the wireless flash control and triggering Navigator X system. It operates at the radio frequency of 2.4GHz and ensures effective range of communication of up to 100 meters. As a result, Stroboss 60 S can be used both as MASTER and SLAVE flash in the Quadralite Navigator X system. Plus, it may be used as a part of the wireless flash control and triggering systems: Sony Wireless Lighting System – WL.

Quadralite Stroboss 60 S flash works best with Quadralite Navigator X radio transceiver which allows wireless control and triggering including High-Speed Sync and Multi modes*.

Key Product Features:

- Compatibility with Sony ADI cameras (flash exposure compensation, synchro with high shutter speeds HSS, flash bracketing, flash exposure lock, front and rear shutter synchro).
- Compatibility with remote flash control and triggering systems: Sony Wireless Lighting System – WL (MASTER, SLAVE).
- Integrated radio transmitter and receiver (2.4GHz) of the Quadralite Navigator X remote control and triggering system (the flash can work in MASTER and SLAVE modes).
- Triggering through a photocell or via Jack 2.5mm connection.
- Large flash output (GN 60) and stable color temperature (5600K ± 200K).
- Full control over the flash output in the manual mode (adjustment from 1/1 to 1/128 at 1/3 EV steps).
- Flexible flash head (horizontal tilt from 0° to 360° and vertical tilt from -7° to 90°).
- 20-200 mm zoom and a built-in panel with the dispersing capacity to 14mm.
- Firmware update through USB interface.

Kit includes:

- Stroboss 60n flash
- stand
- bag

Warranty:

- 2 years



5 901698 711009 >

5901698711009

Specification:

	Quadralite Stroboss 60 S
Compatible systems	Sony ADI (Multi-interface hot-shoe)
Guide number (ISO100, @200mm)	60m
Zoom	20 – 200mm (14mm with wide panel)
Flash head til/swing	0° to 360° horizontally, -7° to 90° vertically
Flash modes	ADI/M/Multi
Control range of flash energy in M	7 f-stops, 1/1 – 1/128 in 1/3EV intervals
Recycle time	~ 0.1~2.6s with eneloop Pro AA 2500 mAh batteries
Color Temperature	5600 K ± 200K
Flash Duration t0.1	Od 1/300 (1/1) ~ 1/20000 s (1/128)
Max sync speed	1/8000s in HS mode
Triggering Method	Optical (Master flash control)
	Wireless (with Navigator X receiver)
Power supply	4x LR6 (AA) batteries
Battery Efficiency	Approx. 200~230 flashes at full power
Dimensions	64x76x190mm
Weight (excl. Battery)	530g

* third party radio triggers will work only up to cameras x-sync speed, wireless output control and HSS is not supported