

## Quadralite Up! X 700 Kit

It is the most extensive set in our Up! X Kit series. There are two Quadralite Up! X lamps and one Quadralite Up! X 300, three lighting stands, a white transparent umbrella, a softbox, a dish and a brandoors with a grid and coloxr filters. Such a completed set allows for many possibilities of lighting settings and at the same time is an ideal introduction to studio photography. More lamps and additional modifiers will allow you to diversify photos during the session.



Up! X 200 and Up! X 300 lamps are extremely compact and light. Dedicated especially to amateurs who want to start their adventure in studio photography. They will also work well as extra gear to studio equipment for professionals. More power allows you to illuminate objects from a greater distance. By integral Navigator X receiver they can be easily wirelessly triggered and changed the flash power. The built-in Bowens mount allows you to expand your studio with additional light modifiers, such as Softboxes or Beauty Dishes.



- **The kit sold includes:**

- 2x Quadralite Up! X 200 lamp,
- 1x Quadralite Up! X 300 lamp,
- 3x light stand 200 cm high 200 cm,
- 1x white transparent umbrella: Ø 81 cm,
- 1x softbox 60x60 cm,
- 1x brandoors with grid and color filters,
- 1x dish: Ø 18 cm,
- 1x dish: Ø 15 cm,
- 3x sync cable,
- 3x power cable,
- 3x pilot halogen,
- 6x spare fuses,
- user manual.



5901698718749

**EAN:** 5901698718749

**Warranty:** 2 Years

| Specification:                     | Up! X 200                     | Up! X 300                 |
|------------------------------------|-------------------------------|---------------------------|
| Product type                       | Studio flash                  |                           |
| Flash qualities                    |                               |                           |
| Max energy output                  | 200 Ws (J)                    | 300 Ws (J)                |
| Guide number                       | 53 m                          | 58 m                      |
| Color temperature                  | 5600K ± 300K                  |                           |
| Flash Duration (t=0.5)             | 1/700s @ 1/32 ~ 1/1600s @ 1/1 |                           |
| Energy range                       | 1/32 (6 Ws) ~ 1/1 (200Ws)     | 1/32 (9 Ws) ~ 1/1 (300Ws) |
| Recycle time                       | 0.3 s – 1.2 s                 |                           |
| Flash modes                        | Manual (M)                    |                           |
| Modeling light                     |                               |                           |
| Type                               | Halogen                       |                           |
| Max power                          | 150 W (E27)                   |                           |
| Color temperature                  | ok. 3300 K                    |                           |
| Modes                              | manual/proportional/OFF       |                           |
| Wireless control and communication |                               |                           |
| Navigator X                        | Yes (Build-in)                |                           |
| Mode                               | Slave/OFF                     |                           |
| Channels                           | 32                            |                           |
| Groups                             | 16                            |                           |

|                           |                            |        |
|---------------------------|----------------------------|--------|
| Powering                  |                            |        |
| Powering source           | AC 220V - 240 V ~ 50Hz     |        |
| Miscellaneous             |                            |        |
| Sync socket               | Yes (3,5mm Jack)           |        |
| Slave cell                | Yes                        |        |
| Cooling                   | Passive                    |        |
| Ready indicator           | Visual and sound signal    |        |
| Display                   | Dot-matrix hi-contrast LCD |        |
| Temperature range         | +10°C - +40°C              |        |
| Diameter x Height x Width | 115mm x 186mm x 280mm      |        |
| Weight                    | 1.35 kg                    | 1.4 kg |

\* Metered @ 1/1 of power and 7' reflector